

New odourless
formula

Reconstituted
from real wood



Excellent adhesion



Does not shrink



Extremely hard
when dry



Quick drying time



Multi-Purpose Wood Filler



PRODUCT DESCRIPTION

- Blanchon **Multi-Purpose Wood Filler** has been especially designed to fill gaps, cracks and holes in furniture, woodwork or wood floors. Damaged parts of furniture (angles, keyholes, etc.) can be repaired or remodelled with **Multi-Purpose Wood Filler**.
- **Multi-Purpose Wood Filler** is suitable for all types of work; it is easy to use with excellent adhesion to all wood species.
- **Multi-Purpose Wood Filler** is made from real wood so when dry behaves just like wood: it can be nailed, screwed, sanded, sawed, painted, stained, varnished, and waxed...
- Available in 5 colours: natural, light oak, medium oak, dark oak, pine.

SURFACE PREPARATION

- Wood must be clean, dry and clear of any existing coatings (varnish, paint, wax, wood floor varnish, etc.).
- New tropical woods should be degreased using acetone before applying **Multi-Purpose Wood Filler**. Traces of resin on softwood (pine, fir, pitch pine, etc.) should also be removed.

DIRECTIONS FOR USE

- **Multi-Purpose Wood Filler** is ready to use. If necessary, mix the product before use. Only use in well ventilated areas.
- Apply **Multi-Purpose Wood Filler** quickly using a spatula wider than the gap to fill.
- No need to "work" **Multi-Purpose Wood Filler**, it dries very quickly.
- Remove any excess with sandpaper, as soon as the product is dry.
- If the repaired area needs to be stained, sand carefully around the area to avoid a "halo" effect.
- Fill deep holes in several stages or pack then fill.
- Reseal the container properly after use.

Cleaning of tools

- Clean tools immediately after use with water. Do not reuse containers.
- Protecting the environment: - Wring out cloths and wipe tools thoroughly after application.
 - Rinse with a little water in a container and allow the water to evaporate.
 - The dry residue can normally be discarded in the waste bin.
 - Seal the container properly after use.
 - Dispose of empty containers thoughtfully.
 - Do not discharge into drains.

DRYING TIME

- Around 30 minutes (for 2 mm holes).
- Recoverable when filler is dry enough to sand.

STORAGE

- Protect from frost (be careful if stored in vehicles).
- Carefully seal the container after use.

Blanchon

Multi-Purpose Wood Filler

TECHNICAL DATA

USE	Filling all defects and gaps in most wood species
RESIN TYPE	Water-based
AFNOR CLASSIFICATION	Family 1, class 7b2
REGULATORY INFORMATION	Refer to the relevant Material Safety Data Sheet (also available on www.blanchon.com or www.quickfds.com)
TYPE OF PRODUCT	Single component product, no mixing required
FLUIDITY	Thick
RECOATABLE	As soon as sanding is possible

Technical Data Sheet issued on the 10.05.2012.

The information provided in this Technical Data Sheet is given in good faith for information purposes only. In no case whatsoever can this information be considered as a guarantee given by us nor engage our responsibility when our products are used. Since we are constantly striving to improve our products, the information given here may be subject to modification without prior notice. This Technical Data Sheet cancels and supersedes all previous versions.

Respect
for people and
the environment



www.blanchon.com

28 rue Charles Martin - BP 105
69192 SAINT-FONS CEDEX - FRANCE
Tél. 04 72 89 06 00 - Fax 04 78 70 07 18
Export Lines: Tel: (0033) 472 89 06 09
Fax: (0033) 472 89 06 02

Blanchon

BLANCHON S.A. - Est. 1832 - A stock company with a board of directors and a supervisory board, with a registered capital of € 4 258 258
390 112 886 RCS LYON - APE 2030 Z - E-mail: info.uk@blanchon.com
Internet : www.blanchon.com